

CORE 5 Specifications

Physical

Size (L x W x H)	9.555 × 5.000 × 7.602 in
Weight	12 lbs with GD KG-175Nano

Power

- 95-W with KG-175N
- Integrated power supply with electromagnetic interference (EMI) filtering

Environmental

- **Temperature:** -40deg C to 71deg C (operational); -40deg C to 71deg C (storage)
- **Humidity:** 95% at 60deg C
- **Altitude:** 50,000 ft (operational)
- **Explosive Atmosphere:** Per MIL-STD-810 Method 511.5
- **Vibration:** Per MIL-STD-810 Method 514.6
- **Shock:** Per MIL-STD-810 Method 516.6: 20 G (operational)
- **Acceleration:** Per MIL-STD-810 Method 513.6: 5.5 G (operational)
- **Sand/Dust:** Per MIL-STD-810 Method 510.5 Blowing Sand
- **Salt Fog:** Per MIL-STD-810 Method 509.5

Configuration

- Supports multi-domain (ciphertext), NSA-secure architecture
- Two fully independent security domains
- Intel Core i7-13800HRE Processor
- 1 TB NVMe onboard
- 64 GB RAM onboard

Operational I/O

- Seven 1GB Ethernet ports per enclave
- One USB 3.0 interface per enclave
- One RS-232, one RS-422 interface per enclave
- 4 GPIO (2 in, 2 out) interfaces per enclave

Management I/O

- One USB 3.0 interface per enclave
- One mini display port per enclave
- One 1GB Ethernet port per enclave

SDN Components

OS: Red Hat Enterprise Linux running kernel-based virtual machines, PODMAN containers, and/or Docker containers

Processor: Intel Core i7-13800HRE Processor

RAM: 64 GB RAM onboard

SDD: 1 TB NVMe onboard

Routing: Border Gateway Protocol (BGP), Open Shortest Path First (OSPF), Enhanced Interior Gateway Routing Protocol (EIGRP), policy-based routing, IPv6, Virtual Route Forwarding-Lite (VRF-Lite), multicast, LISP, and Generic Routing Encapsulation (GRE)

Addressing: Dynamic Host Configuration Protocol (DHCP), Domain Name System (DNS), Network Address Translation (NAT), 802.1Q VLAN, Ethernet Virtual Connection (EVC), and VXLAN

VPN: IPsec VPN, Dynamic Multipoint VPN (DMVPN), Easy VPN, SSL VPN, and FlexVPN

MPLS: MPLS VPN, virtual routing/forwarding (VRF), and Bidirectional Forwarding Detection (BFD)

Security: Cisco IOS Zone-Based Policy Firewall, access control list (ACL), RADIUS, TACACS+, and authentication, authorization, and accounting (AAA)

Other SDN Components

- Support for boundary defense protection system and deep packet inspection (e.g., Cisco ASA or Palo Alto)
- WAN optimization and acceleration (e.g., Riverbed VCX)
- Native Linux bridging for VLAN tagging, isolation, trunking, and separation of system management plane from data plane

Compliance

- TEMPEST-compliant NSTISSAM 1/92 Level I design
- MIL-STD-810, MIL-STD-461, MIL-STD-464, MIL-STD-704

Optional Capabilities for CORE 5

Fuse Network Provisioner

A software utility that ingests a platform's mission computer configuration information and dynamically reformats it into a device- and vendor-agnostic data scheme before reformatting to the formats appropriate to each module in the network stack. With the innovative Fuse Network Provisioner, even advanced network configurations are faster, easier, and more secure than having to pre-configure each device for every platform.

- **Hardware is vendor-agnostic.** Works with Cisco, Juniper, Palo Alto, FRR routers and any others
- **Universal.** Works with legacy and modern mission computers
- **Multi-layer support.** Extends templates beyond routers to firewalls, radios, and application layers
- **Common language.** Uses one ontology for all network components, simplifying links between the network components to support transparency and troubleshooting

Embedded Firewall

Optional embedded firewall provides extra security for communications.

Expansion interfaces

Each CORE 5 enclaves has an mPCIe expansion slot to support additional capabilities including:

- MIL-STD-1553B
- CAN Bus
- RS-485
- Software Defined Radio
- FPGA expansion

